

Network cable - NBC-MS/10,0-94B/R4AC SCO US - 1409864

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Network cable, Ethernet CAT5, Ethernet CAT5e, 8-position, PUR halogen-free, water blue RAL 5021, shielded, Plug Straight M12 SPEEDCON / IP67, Coding: A, on Plug Straight RJ45 / IP20, Cable length: 10 m



Key commercial data

| | |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 500.0 GRM |
| Custom tariff number | 85444290 |
| Country of origin | United States |

Technical data

Dimensions

| | |
|-----------------|------|
| Length of cable | 10 m |
|-----------------|------|

Ambient conditions

| | |
|----------------------|-----------------------|
| Degree of protection | IP65 (M12 connector) |
| | IP67 (M12 connector) |
| | IP20 (RJ45 connector) |

General data

| | |
|-----------------------|--------------------------------|
| Rated current at 40°C | 1 A |
| Rated voltage | 30 V |
| Number of positions | 8 |
| Signal type/category | Ethernet CAT5 (IEC 11801:2002) |
| | Ethernet CAT5e (TIA 568B:2001) |
| Standards/regulations | M12 connector IEC 61076-2-101 |

Characteristics head 1

| | |
|-----------|-----------------------------------|
| Head type | Plug Straight M12 SPEEDCON / IP67 |
|-----------|-----------------------------------|

Network cable - NBC-MS/10,0-94B/R4AC SCO US - 1409864

Technical data

Characteristics head 1

| | |
|--------|--------------|
| Coding | A (Standard) |
|--------|--------------|

Characteristics head 2

| | |
|-----------|---------------------------|
| Head type | Plug Straight RJ45 / IP20 |
|-----------|---------------------------|

Cable

| | |
|---|--|
| Cable type | Ethernet, flexible, CAT5e |
| Cable type (abbreviation) | 94B |
| UL AWM style | 20963 (80°C/30 V) |
| Signal type/category | Ethernet CAT5 (IEC 11801:2002), 0.1 Gbps Ethernet CAT5e (TIA 568B:2001), 0.1 Gbps |
| Cable structure | 4x2xAWG26/7; SF/UTP |
| Conductor cross section | 4x 2x 0.14 mm ² |
| AWG signal line | 26 |
| Conductor structure signal line | 7x 0.16 mm |
| Core diameter including insulation | 0.98 mm |
| Thickness, insulation | 0.25 mm |
| Wire colors | white/blue-blue, white/orange-orange, white/green-green, white/brown-brown |
| Twisted pairs | 2 cores to the pair |
| Overall twist | 4 pairs |
| Shielding | Aluminum-coated foil, tinned copper braided shield |
| Optical shield covering | 70 % |
| External sheath, color | water blue RAL 5021 |
| Outer sheath thickness | 1 mm |
| External cable diameter D | 6.4 mm ±0.2 mm |
| Smallest bending radius, fixed installation | 25.6 mm |
| Smallest bending radius, movable installation | 51.2 mm |
| Tensile strength short-term/long-term | ≤ 100 N |
| Cable weight | 47 kg/km |
| Outer sheath, material | PUR |
| Material conductor insulation | PE |
| Conductor material | Bare Cu litz wires |
| Insulation resistance | ≥ 500 MΩ*km |
| Loop resistance | ≤ 290 Ω (per kilometer) |
| Working capacitance | 48 nF (At 1 kHz) |
| Wave impedance | 100 Ω ±5 Ω (at 100 MHz) |
| Signal runtime | 5.3 ns/m |
| Coupling resistance | ≤ 100.00 mΩ/m (At 10 MHz) |

Network cable - NBC-MS/10,0-94B/R4AC SCO US - 1409864

Technical data

Cable

| | |
|---|---|
| Nominal voltage, cable | ≤ 100 V |
| | 300 V (Outer cable sheath) |
| Test voltage Core/Core | 700 V (50 Hz, 1 min.) |
| Test voltage Core/Shield | 700 V (50 Hz, 1 min.) |
| Flame resistance | IEC 60332-1-2 |
| Halogen-free | According to IEC 60754-1 |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -20 °C ... 80 °C (cable, flexible installation) |
| Ambient temperature (installation) | -20 °C ... 80 °C |
| Ambient temperature (storage/transport) | -20 °C ... 80 °C |


Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002586 |
| ETIM 5.0 | EC000830 |


Drawings

Schematic diagram



Connector pin assignment plug RJ45

Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side


Network cable - NBC-MS/10,0-94B/R4AC SCO US - 1409864

Cable cross section




Ethernet, flexible, CAT5e [94B]

Dimensioned drawing




Plug, M12 x 1, straight, shielded

Dimensioned drawing



RJ45 connector, IP20

Circuit diagram



Contact assignment of the M12 and RJ45 plug