

## Marshalling distributors - ZRV 8 WH - 3025957

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Marshalling distributors, Nom. voltage: 250 V, Nominal current: 10 A, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 14 - 26, Connection type: Spring-cage connection, Width: 7.62 mm, Length: 225 mm, Color: white, Assembly: NS 35/7,5, NS 35/15

The illustration shows the version in gray



### Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	78.0 GRM
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### General

Number of levels	8
Number of connections	16
Color	white
Insulating material	PC
Inflammability class according to UL 94	V0
Rated surge voltage	4 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	IIIa
Connection in acc. with standard	IEC 60947-7-1
Maximum load current (lower level)	10 A
Additional text	with 1.5 mm <sup>2</sup> conductor cross section
Nominal current I <sub>N</sub> (lower level)	10 A

## Marshalling distributors - ZRV 8 WH - 3025957

### Technical data

#### General

Nominal voltage $U_N$	250 V
Open side panel	ja

#### Dimensions

Width	7.62 mm
Length	225 mm
Height NS 35/7,5	82 mm
Height NS 35/15	89.5 mm

#### Connection data

Conductor cross section solid min.	0.14 mm <sup>2</sup>
Conductor cross section solid max.	1.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	1 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.14 mm <sup>2</sup>
Conductor cross section stranded, with ferrule without plastic sleeve max.	0.75 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.14 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve max.	0.75 mm <sup>2</sup>
Connection method	Spring-cage connection
Stripping length	8 mm

### Classifications

#### eCl@ss

eCl@ss 4.0	27141124
eCl@ss 4.1	27141124
eCl@ss 5.0	27141124
eCl@ss 5.1	27141124
eCl@ss 6.0	27141124
eCl@ss 7.0	27141124
eCl@ss 8.0	27141124

#### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC002567
ETIM 5.0	EC002567

## Marshalling distributors - ZRV 8 WH - 3025957

### Classifications

#### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

### Drawings

#### Circuit diagram

